



VANGTON INDUSTRY CO., LTD

SHOUGUANG ROAD 3-3127, QINGDAO CITY, CHINA

TEL. +86(532)88913303 FAX.+86(532)88913363 MAIL.SALES@VANGTON.COM

DRUM ROTARY DRYER



Drum dryer is used for drying out liquids from raw materials with drying drum. In the drum-drying process, pureed raw ingredients are dried at relatively low temperatures over rotating, high-capacity drums that produce sheets of drum-dried product. The drum dryer is suitable for fuel plant, fertilizer plant, chemical plant, pharmaceutical and other industries.

Model	DR650B	DR1200B	HG1200	HG1500	HG1800	HG2000
Initial moisture	30%-40%	30%-40%	35%-45%	35%-45%	35%-45%	35%-45%
Final Drying Moisture	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%
Fan power	7.5KW	7.5KW	18.5KW	22KW	37KW	45KW
Drum Power	2.2KW	5.5KW	5.5KW	7.5KW	11KW	12KW
Drum size	0.65M*10M	1.2M*10M	1.2M*10M	1.5M*12M	1.8M*12M	2M*12M
Drying Speed	500-600KG/ H	800-1200KG /H	1300-1500K G/H	1500-2000K G/H	2000-2500K G/H	2800-3000K G/H
Machine Weight	3900KG	5500KG	7400KG	11600KG	23800KG	28500KG